

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
3 October 2002 (03.10.2002)

PCT

(10) International Publication Number  
WO 02/077356 A1(51) International Patent Classification: D06L 1/02, 1/04,  
C11D 11/00, D06F 43/00, C11D 7/50 // 3/16

(21) International Application Number: PCT/US02/04620

(22) International Filing Date: 15 February 2002 (15.02.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09/813,666 21 March 2001 (21.03.2001) US(71) Applicant: GENERAL ELECTRIC COMPANY  
[US/US]; 1 River Road, Schenectady, NY 12345 (US).(72) Inventors: PERRY, Robert, J.; 2115 Niskayuna Drive,  
Niskayuna, NY 12309 (US). HUBBARD, Patricia, A.; 19  
Crestview Drive, West Sand Lake, NY 12196 (US).(74) Agents: WINTER, Catherine, J. et al.; General Electric  
Company, 3135 Easton Turnpike W3C, Fairfield, CT 06431  
(US).(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,  
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN,  
YU, ZA, ZM, ZW.(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR,  
GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent  
(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR,  
NE, SN, TD, TG).

## Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VAPOR PHASE SILOXANE DRY CLEANING PROCESS

(57) Abstract: The process of the present invention is directed to a dry cleaning process, comprising the use of volatile cyclic, linear or branched siloxanes in the vapor phase for the cleaning of soiled or stained fabrics. The linear or branched siloxanes have the formula:  $M_{2x+y+z}D_xT_yQ_z$  wherein: M is  $R^1SiO_{1/2}$ ; D is  $R^2R^3SiO_{2/2}$ ; T is  $R^4SiO_{3/2}$ ; and Q is  $SiO_{4/2}$ .  $R^1$ ,  $R^2$ ,  $R^3$  and  $R^4$  are each independently a monovalent hydrocarbon radical having from one to forty carbon atoms; and x and y are each integers, wherein  $0 < x < 10$  and  $0 < y < 10$ , and  $0 < z < 10$ . While the cyclic siloxanes have the formula (1) wherein  $R^5$ ,  $R^6$ ,  $R^7$  and  $R^8$  are each independently a monovalent hydrocarbon group having from one to forty carbon atoms; and a and b are each integers wherein  $0 < a < 10$  and  $0 < b < 10$ , provided that  $3 < (a + b) < 10$ .

WO 02/077356 A1

## VAPOR PHASE SILOXANE DRY CLEANING PROCESS

## TECHNICAL FIELD

The present invention is directed to a dry cleaning process, more specifically, to a siloxane vapor phase based process, for use in dry cleaning.

## BACKGROUND

Current dry cleaning technology uses perchloroethylene ("PERC") or petroleum-based materials as the cleaning solvent. PERC suffers from toxicity and odor issues. The petroleum-based products are not as effective as PERC in cleaning garments.

Cyclic siloxanes have been reported as spot cleaning solutions, see US 4,685,930, and as dry cleaning fluids in dry cleaning machines, see US 5,942,007. Other patents disclose the use of silicone soaps in petroleum solvents, see JP 09299687, and the use of silicone surfactants in super critical carbon dioxide solutions has been reported, see, for example, US 5,676,705 and Chem. Mark. Rep., 15 Dec 1997, 252(24), p. 15. Non-volatile silicone oils have also been used as the cleaning solvent requiring removal by a second washing with perfluoroalkane to remove the silicone oil, see JP 06327888.

Numerous other patents have issued in which siloxanes or organomodified silicones have been present as addenda in PERC or petroleum based dry cleaning solvents, see, for example, WO 9401510; US 4911853; US 4005231; US 4065258.

There is a continued interest in decreasing the need for large quantities of solvents used in dry cleaning processes.

## SUMMARY OF THE INVENTION

The process of the present invention is directed to a cleaning process, comprising the use of a volatile cyclic, linear or branched siloxane in the vapor phase for the cleaning of articles.

Further, the present invention provides for a process for cleaning soiled  
5 articles of manufacture comprising:

- 
- a) contacting the soiled article of manufacture with a vapor phase silicone compound;
  - b) allowing the vapor phase silicone compound in contact with the soiled article of manufacture to condense to the liquid phase becoming thereby a  
10 condensed silicone liquid; and
  - c) draining the condensed silicone liquid away from the article of manufacture whereby the soiled article of manufacture is cleaned.

In another embodiment the present invention provides for a process for cleaning soiled garments comprising:

- 15 a) contacting the soiled garment with a vapor phase silicone compound;
- b) allowing the vapor phase silicone compound in contact with the soiled garment to condense to the liquid phase becoming thereby a condensed silicone liquid; and
- c) draining the condensed silicone liquid away from the garment whereby  
20 the soiled garment is cleaned.

## DETAILED DESCRIPTION OF THE INVENTION

The compounds useful in the practice of the present invention may be linear, branched or cyclic volatile siloxane compounds. In general those siloxanes that are volatile and suitable for use in the practice of the present invention are those siloxanes that are volatile at room temperature, i.e. about 25 °C. Volatility is a quantitative measurement at a given temperature and thus broadly defined involves a partial pressure or vapor pressure, i.e. a pressure below 760 mm Hg, at a given temperature. Broadly, volatile siloxanes are those siloxanes that have a vapor pressure or partial pressure (as used herein the two terms are interchangeable) above 0.01 mm Hg at a temperature of 20 °C.

Compounds suitable as the linear or branched, volatile siloxane solvent of the present invention are those containing a polysiloxane structure that includes from 2 to 20 silicon atoms. Preferably, the linear or branched, volatile siloxanes are relatively volatile materials, having, for example, a boiling of below about 300°C point at a pressure of 760 millimeters of mercury ("mm Hg").

In one embodiment, the linear or branched, volatile siloxane comprises one or more compounds of the structural formula (I):



wherein:

M is  $R^1_3SiO_{1/2}$ ;

D is  $R^2R^3SiO_{2/2}$ ;

T is  $R^4SiO_{3/2}$ ;

and Q is  $\text{SiO}_{4/2}$

$\text{R}^1$ ,  $\text{R}^2$ ,  $\text{R}^3$  and  $\text{R}^4$  are each independently a monovalent hydrocarbon radical having from one to forty carbon atoms; and

x and y are each integers, wherein  $0 \leq x \leq 10$  and  $0 \leq y \leq 10$  and  $0 \leq z \leq 10$ .

5        Suitable monovalent hydrocarbon groups include linear hydrocarbon radicals, branched hydrocarbon radicals, monovalent alicyclic hydrocarbon radicals, monovalent and aromatic or fluoro containing hydrocarbon radicals. Preferred monovalent hydrocarbon radicals are monovalent alkyl radicals, monovalent aryl radicals and monovalent aralkyl radicals.

10        As used herein, the term "(C<sub>1</sub>-C<sub>6</sub>)alkyl" means a linear or branched alkyl group containing from 1 to 6 carbons per group, such as, for example, methyl, ethyl, propyl, iso-propyl, n-butyl, iso-butyl, sec-butyl, tert-butyl, pentyl, hexyl, preferably methyl.

15        As used herein, the term "aryl" means a monovalent unsaturated hydrocarbon ring system containing one or more aromatic or fluoro containing rings per group, which may optionally be substituted on the one or more aromatic or fluoro containing rings, preferably with one or more (C<sub>1</sub>-C<sub>6</sub>)alkyl groups and which, in the case of two or more rings, may be fused rings, including, for example, phenyl, 2,4,6-trimethylphenyl, 2-  
20        isopropylmethylphenyl, 1-pentalenyl, naphthyl, anthryl, preferably phenyl.

25        As used herein, the term "aralkyl" means an aryl derivative of an alkyl group, preferably a (C<sub>2</sub>-C<sub>6</sub>)alkyl group, wherein the alkyl portion of the aryl derivative may, optionally, be interrupted by an oxygen atom, such as, for example, phenylethyl, phenylpropyl, 2-(1-naphthyl)ethyl, preferably phenylpropyl, phenyloxypropyl, biphenyloxypropyl.

In another embodiment, the monovalent hydrocarbon radical is a monovalent ( $C_1$ - $C_6$ )alkyl radical, most preferably, methyl.

In another embodiment, the linear or branched, volatile siloxane comprises one or more of, hexamethyldisiloxane, octamethyltrisiloxane,  
5 decamethyltetrasiloxane, dodecamethylpentasiloxane, tetradecamethylhexasiloxane or hexadecamethylheptasiloxane or


methyltris(trimethylsiloxy)silane. In a more highly preferred embodiment,  
the linear or branched, volatile siloxane of the present invention comprises  
octamethyltrisiloxane, decamethyltetrasiloxane, or  
10 dodecamethylpentasiloxane or methyltris(trimethylsiloxy)silane. In a highly  
preferred embodiment, the siloxane component of the composition of the  
present invention consists essentially of decamethyltetrasiloxane.

Suitable linear or branched volatile siloxanes are made by known  
methods, such as, for example, hydrolysis and condensation of one or more of  
15 tetrachlorosilane, methyltrichlorosilane, dimethyldichlorosilane,  
trimethylchlorosilane, or by isolation of the desired fraction of an equilibrate  
mixture of hexamethyldisiloxane and octamethylcyclotetrasiloxane or the like  
and are commercially available.

Compounds suitable as the cyclic siloxane component of the present  
20 invention are those containing an oligomeric or polysiloxane ring structure  
that includes from 2 to 20 silicon atoms in the ring. Preferably, the linear,  
branched and cyclic siloxanes are relatively volatile materials, having, for  
example, a boiling point of below about 300°C at a pressure of 760 millimeters  
of mercury ("mm Hg"). Thus for the purposes of defining a volatile siloxane  
25 compound useful in the practice of the process of the present invention a  
volatile siloxane, whether linear branched or cyclic has a vapor pressure

ranging from 0.01 to 760 mm Hg at a temperature ranging from about 10 °C to about 300 °C.

In another embodiment, the cyclic siloxane comprises one or more compounds of the structural formula (II):



wherein:

R<sup>5</sup>, R<sup>6</sup>, R<sup>7</sup> and R<sup>8</sup> are each independently a monovalent hydrocarbon group having from one to forty carbon atoms; and

10 a and b are each integers wherein  $0 \leq a \leq 10$  and  $0 \leq b \leq 10$ , provided that  $3 \leq (a + b) \leq 10$ .

15 In yet another embodiment, the cyclic siloxane comprises one or more of, octamethylcyclotetrasiloxane, decamethylcyclopentasiloxane, dodecamethylcyclohexasiloxane, tetradecamethylcycloheptasiloxane. In a more highly preferred embodiment, the cyclic siloxane of the present invention comprises octamethylcyclotetrasiloxane or decamethylcyclopentasiloxane. In yet another embodiment, the cyclic siloxane component of the composition of the present invention consists essentially of decamethylcyclopentasiloxane.

20 Suitable cyclic siloxanes are made by known methods, such as, for example, hydrolysis and condensation of alkylhalosilanes, e.g. dimethyldichlorosilane, and are commercially available.

The process of the invention involves generation of a gas phase silicone by a combination of heating the silicone in a solvent reservoir and optionally reducing pressure so as to allow the silicone to vaporize followed by contacting the silicone vapors with the garment to be cleaned. While the  
5 formula describing compounds useful in the process of the present invention has already been described, those compounds useful in the practice of the present invention in one embodiment should have vapor pressures between

about 3.0 mm Hg and about 760 mm Hg at temperatures ranging from about  
20 °C to about 100 °C. In a second embodiment those compounds useful in  
10 the practice of the present invention should have vapor pressures between about 0.01 mm Hg and about 760 mm Hg at temperatures ranging from about 20 °C to about 270 °C. In a third embodiment those compounds useful in the practice of the present invention should have vapor pressures  
between about 1.0 mm Hg and about 760 mm Hg at temperatures ranging  
15 from about 20 °C to about 134 °C. In a fourth embodiment those compounds useful in the practice of the present invention should have vapor pressures between about 0.01 mm Hg and about 760 mm Hg at temperatures ranging from about 20 °C to about 264 °C.

Alternatively, other methods known in the art can be employed to  
20 form vapors of silicones including mechanical means.

The vapors of the compounds of the present invention thus formed, either at atmospheric pressure or at reduced pressure, are allowed to contact the fabric to be cleaned for a specified time wherein these same vapors  
condense in the fabric, dissolving the soiling material or stain and draining  
25 away from the fabric, after which time the articles are removed, cooled as needed, and dried by various methods known in the art such as air drying, heated drying and the like. In one embodiment, the process of the present invention may be performed at a constant pressure. In another embodiment



the process of the present invention is performed at a pressure that is varied among the steps of the process, e.g. initially contacting the garment to be cleaned with a vapor at a pressure below atmospheric followed by raising the pressure to atmospheric pressure to condense the vapor in the garment and  
5 allow the cleaning fluids to drain away from the garment.

Alternatively, the articles remain in the cleaning vessel and the silicone or silicone containing solvent is removed by various means and the articles are dried in the cleaning vessel as is commonly seen in typical dry cleaning machines.

10 An article, such as for example, a textile or leather article, typically, a garment, is cleaned by contacting the article with the vapors of the composition of the present invention. In a preferred embodiment, the articles to be cleaned include textiles made from natural fibers, such as for example, cotton, wool, linen and hemp, from synthetic fibers, such as, for example,  
15 polyester fibers, polyamide fibers, polypropylene fibers and elastomeric fibers, from blends of natural and synthetic fibers, from natural or synthetic leather or natural or synthetic fur.

The article and dry cleaning composition are then separated, by, for example, one or more of draining and centrifugation. In a preferred  
20 embodiment, separation of the article and dry cleaning composition is followed by the application of heat, preferably, heating to a temperature of from 15°C to 120°C, preferably from 20°C to 100°C, or reduced pressure, preferably, a pressure of from 1 mm Hg to 750 mm Hg, or by application of both heat and reduced pressure, to the article.

25 Testing for oil soluble stain removal was accomplished using a blue 50/50 cotton/poly cloth and a red satin fabric. The approximately 2 inch square samples were stained with motor oil, suspended by wires in a large

glass vessel equipped with a thermometer, and condensing unit capable of condensing the volatile silicone solvent. The articles were positioned such that the solvent vapors saturated the article but were not contacted by the returning, condensed solvent.

5           The process of the present invention is not limited to the cleaning of garments or articles of clothing, it may be applied to any article of manufacture contaminated with a silicone soluble contaminant that may be  
10           subjected to the process of the present invention wherein the contaminant is dissolved in the silicone compound and drained away, thereby removing the contaminant from the article of manufacture.

The following examples are to illustrate the invention and are not to be construed as limiting the claims.

#### EXAMPLES

##### Example 1 - Atmospheric pressure, cyclic solvent

15           Samples of red satin and blue cotton/poly fabrics were treated with motor oil which was allowed to stain for 18 hours then attached to a wire holder and suspended above a reservoir of D5. The solvent was heated to boiling and the vapors allowed to contact the stained fabrics for 5 minutes. After this time, the heat was removed, the vessel cooled and the samples removed and air dried and evaluated. All traces of the oil were removed from  
20           both fabrics. There was some extraction of the red dye from the satin fabric.

##### Example 2 - Reduced Pressure, cyclic solvent

          Samples of red satin and blue cotton/poly fabrics were treated with motor oil which was allowed to stain for 18 hours then attached to a wire holder and suspended above a reservoir of D5. The pressure in the system

was reduced to 1-2 mm Hg and the temperature of the solvent reservoir was raised to 70-80 °C. The vapors were allowed to contact the stained fabrics for 5 minutes. After this time, the heat was removed, the vessel cooled and the samples removed and air dried and evaluated. All traces of the oil were removed from both fabrics. No extraction of the red dye from the satin fabric was observed.

### Example 3 - Reduced Pressure, linear solvent


---

Samples of red satin and blue cotton/poly fabrics were treated with motor oil which was allowed to stain for 18 hours then attached to a wire holder and suspended above a reservoir of MD2M. The pressure in the system was reduced to 1-2 mm Hg and the temperature of the solvent reservoir was raised to 70-80 °C. The vapors were allowed to contact the stained fabrics for 5 minutes. After this time, the heat was removed, the vessel cooled and the samples removed and air dried and evaluated. All traces of the oil were removed from both fabrics. No extraction of the red dye from the satin fabric was observed.

Having described the invention, that which is claimed is:

1. A process for cleaning soiled garments comprising:
  - a) contacting the soiled garment with a vapor phase silicone compound;
  - b) allowing the vapor phase silicone compound in contact with the soiled garment to condense to the liquid phase becoming thereby a condensed silicone liquid; and
  - c) draining the condensed silicone liquid away from the garment whereby the soiled garment is cleaned.

2. The process of claim 1 wherein the silicone compound has the formula:



wherein:

M is  $R^1_3SiO_{1/2}$ ;


D is  $R^2R^3SiO_{2/2}$ ;

T is  $R^4SiO_{3/2}$ ;

and Q is  $SiO_{4/2}$

$R^1$ ,  $R^2$ ,  $R^3$  and  $R^4$  are each independently a monovalent hydrocarbon radical having from one to forty carbon atoms; and x and y are each integers, wherein  $0 \leq x \leq 10$  and  $0 \leq y \leq 10$  and  $0 \leq z \leq 10$ .

3. The process of claim 1 wherein the silicone compound has the formula:



wherein:

R<sup>5</sup>, R<sup>6</sup>, R<sup>7</sup> and R<sup>8</sup> are each independently a monovalent hydrocarbon group  
 5 having from one to forty carbon atoms; and

a and b are each integers wherein  $0 \leq a \leq 10$  and  $0 \leq b \leq 10$ , provided that  $3 \leq (a + b) \leq 10$ .

4. The process of claim 2 wherein each of the steps a), b) and c) are  
 10 independently conducted at a temperature ranging from about 10 °C to about 300 °C.

5. The process of claim 3 wherein each of the steps a), b) and c) are  
 independently conducted at a temperature ranging from about 10 °C to about 300 °C.

6. The process of claim 4 wherein each of the steps a), b) and c) are  
 15 independently conducted at a pressure ranging from about 0.01 mm Hg to about 760 mm Hg.

7. The process of claim 5 wherein each of the steps a), b) and c) are  
 independently conducted at a pressure ranging from about 0.01 mm Hg to about 760 mm Hg.

8. The process of claim 6 wherein the silicone compound is selected from the group consisting of hexamethyldisiloxane, octamethyltrisiloxane, decamethyltetrasiloxane, dodecamethylpentasiloxane, tetradecamethylhexasiloxane, hexadecamethylheptasiloxane and methyltris(trimethylsiloxy)silane.

9. The process of claim 7 wherein the silicone compound is selected from the group consisting of hexamethyldisiloxane, octamethyltrisiloxane, decamethyltetrasiloxane, dodecamethylpentasiloxane, tetradecamethylhexasiloxane, hexadecamethylheptasiloxane and methyltris(trimethylsiloxy)silane.

10. A process for cleaning soiled articles of manufacture comprising:

- a) contacting the soiled article of manufacture with a vapor phase silicone compound;
- b) allowing the vapor phase silicone compound in contact with the soiled article of manufacture to condense to the liquid phase becoming thereby a condensed silicone liquid; and
- c) draining the condensed silicone liquid away from the article of manufacture whereby the soiled article of manufacture is cleaned.

11. A process for cleaning soiled garments consisting essentially of:

- a) contacting the soiled garment with a vapor phase silicone compound;
- b) allowing the vapor phase silicone compound in contact with the soiled garment to condense to the liquid phase becoming thereby a condensed silicone liquid; and
- c) draining the condensed silicone liquid away from the garment whereby the soiled garment is cleaned.

12. The process of claim 11 wherein the silicone compound has the formula:



wherein:

5 M is  $R^1_3SiO_{1/2}$ ;


D is  $R^2R^3SiO_{2/2}$ ;

T is  $R^4SiO_{3/2}$ ;

and Q is  $SiO_{4/2}$ .

10  $R^1$ ,  $R^2$ ,  $R^3$  and  $R^4$  are each independently a monovalent hydrocarbon radical having from one to forty carbon atoms; and x and y are each integers, wherein  $0 \leq x \leq 10$  and  $0 \leq y \leq 10$  and  $0 \leq z \leq 10$ .

13. The process of claim 11 wherein the silicone compound has the formula:



15 wherein:

$R^5$ ,  $R^6$ ,  $R^7$  and  $R^8$  are each independently a monovalent hydrocarbon group having from one to forty carbon atoms; and

a and b are each integers wherein  $0 \leq a \leq 10$  and  $0 \leq b \leq 10$ , provided that  $3 \leq (a + b) \leq 10$ .

14. The process of claim 12 wherein each of the steps a), b) and c) are independently conducted at a temperature ranging from about 10 °C to about 300 °C.

15. The process of claim 13 wherein each of the steps a), b) and c) are independently conducted at a temperature ranging from about 10 °C to about 300 °C.

~~16. The process of claim 14 wherein each of the steps a), b) and c) are independently conducted at a pressure ranging from about 0.01 mm Hg to about 760 mm Hg.~~

17. The process of claim 15 wherein each of the steps a), b) and c) are independently conducted at a pressure ranging from about 0.01 mm Hg to about 760 mm Hg.

18. The process of claim 16 wherein the silicone compound is selected from the group consisting of hexamethyldisiloxane, octamethyltrisiloxane, decamethyltetrasiloxane, dodecamethylpentasiloxane, tetradecamethylhexasiloxane, hexadecamethylheptasiloxane and methyltris(trimethylsiloxy)silane.

19. The process of claim 17 wherein the silicone compound is selected from the group consisting of hexamethyldisiloxane, octamethyltrisiloxane, decamethyltetrasiloxane, dodecamethylpentasiloxane, tetradecamethylhexasiloxane, hexadecamethylheptasiloxane and methyltris(trimethylsiloxy)silane.



## INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/US 02/04620

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 D06L1/02 D06L1/04 C11D11/00 D06F43/00 C11D7/50  
//C11D3/16

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 D06L C11D D06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DATABASE WPI Section Ch, Week 197826 Derwent Publications Ltd., London, GB; Class A26, AN 1978-46701A XP002206086 & JP 53 056203 A (LION FAT & OIL CO LTD), 22 May 1978 (1978-05-22) abstract	1,2,4,6, 8,10-12, 14,16,18
X	US 5 834 416 A (MORGAN DAVID LEE ET AL) 10 November 1998 (1998-11-10) column 6, line 44 - line 53 claims 1,2	10-12, 14,16,18
X	WO 99 10587 A (LAUBACH BERNADETTE STOREY ;MICELL TECHNOLOGIES (US); DEYOUNG JAMES) 4 March 1999 (1999-03-04) page 8, line 1 - line 32	1,10,11
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

16 July 2002

Date of mailing of the international search report

29/07/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Richards, M

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 02/04620

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	EP 1 092 803 A (UNILEVER PLC ;UNILEVER NV (NL)) 18 April 2001 (2001-04-18) example 3	1,10,11
X	----- DATABASE WPI Section Ch, Week 199439 Derwent Publications Ltd., London, GB; Class A97, AN 1994-312983 XP002206053 & JP 06 238244 A (JAPAN FIELD KK), 30 August 1994 (1994-08-30) abstract	10,11
X	----- DATABASE WPI Section Ch, Week 199608 Derwent Publications Ltd., London, GB; Class M12, AN 1996-073089 XP002206054 & JP 07 328563 A (OLYMPUS OPTICAL CO LTD), 19 December 1995 (1995-12-19) abstract	10,11
X	----- DATABASE WPI Section Ch, Week 199416 Derwent Publications Ltd., London, GB; Class L03, AN 1994-132722 XP002206055 & JP 06 032795 B (JAPAN FIELD KK), 2 May 1994 (1994-05-02) abstract	10,11
X	----- DATABASE WPI Section Ch, Week 199439 Derwent Publications Ltd., London, GB; Class A97, AN 1994-312982 XP002206056 & JP 06 238243 A (JAPAN FIELD KK), 30 August 1994 (1994-08-30) abstract	10,11
A	----- US 5 833 761 A (IMAJO YASUTAKA ET AL) 10 November 1998 (1998-11-10) claims 1-12	1-19
A	----- US 5 676 705 A (RESCH CAROL ET AL) 14 October 1997 (1997-10-14) claims 1-10	1-19
P,A	----- US 2002/004953 A1 (PERRY ROBERT J ET AL) 17 January 2002 (2002-01-17) claims 1-26	1-19
	----- -/--	

Personal Application No  
FBI/US 02/04620

Personal Application No  
FBI/US 02/04620

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 685 930 A (KASPRZAK KENNETH A) 11 August 1987 (1987-08-11) cited in the application claims 1-9	1-19
A	US 5 942 007 A (BERNDT DIETER R ET AL) 24 August 1999 (1999-08-24) cited in the application claims 1-24	1-19

## INTERNATIONAL SEARCH REPORT

 International Application No.  
 PCT/US 02/04620

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 53056203	A	22-05-1978	JP 1157294 C JP 57047960 B	15-07-1983 13-10-1982
US 5834416	A	10-11-1998	NONE	
WO 9910587	A	04-03-1999	AU 9038998 A CA 2302527 A1 EP 1007780 A1 JP 2001514339 T WO 9910587 A1 US 6010542 A US 6001133 A US 6228826 B1	16-03-1999 04-03-1999 14-06-2000 11-09-2001 04-03-1999 04-01-2000 14-12-1999 08-05-2001
EP 1092803	A	18-04-2001	US 6309425 B1 EP 1092803 A1 US 2002023305 A1	30-10-2001 18-04-2001 28-02-2002
JP 6238244	A	30-08-1994	NONE	
JP 7328563	A	19-12-1995	NONE	
JP 6032795	B	02-05-1994	JP 4094779 A	26-03-1992
JP 6238243	A	30-08-1994	NONE	
US 5833761	A	10-11-1998	US 5503681 A AU 673062 B2 AU 6314594 A AU 646246 B2 AU 7475191 A CA 2050333 A1 DE 69126648 D1 DE 69126648 T2 DE 69131853 D1 DE 69131853 T2 EP 0473795 A1 EP 0717128 A2 EP 0717129 A2 EP 0757119 A2 JP 2763270 B2 JP 7275812 A JP 3115781 B2 JP 7275813 A WO 9113697 A1 JP 2723359 B2 KR 145061 B1 KR 9510446 B1 KR 121454 B1 KR 9701233 B1 SG 50628 A1 SG 44844 A1 SG 48276 A1 US 5888312 A US 5769962 A US 5772781 A US 5538024 A	02-04-1996 24-10-1996 07-07-1994 17-02-1994 10-10-1991 17-09-1991 31-07-1997 11-12-1997 20-01-2000 29-06-2000 11-03-1992 19-06-1996 19-06-1996 05-02-1997 11-06-1998 24-10-1995 11-12-2000 24-10-1995 19-09-1991 09-03-1998 17-08-1998 18-09-1995 15-11-1997 04-02-1997 20-07-1998 19-12-1997 17-04-1998 30-03-1999 23-06-1998 30-06-1998 23-07-1996

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

US 02/04620

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5676705	A	14-10-1997	AU 4942996 A 23-09-1996
		CA 2211412 A1 12-09-1996	
		WO 9627704 A1 12-09-1996	
		EP 0813628 A1 29-12-1997	
		FI 973603 A 05-09-1997	
		TR 9700901 T1 21-02-1998	
		US 5683473 A 04-11-1997	
		ZA 9601786 A 05-09-1997	
US 2002004953	A1	17-01-2002	WO 0250366 A1 27-06-2002
US 4685930	A	11-08-1987	AU 585906 B2 29-06-1989
		AU 4981785 A 22-05-1986	
		CA 1239326 A1 19-07-1988	
		DE 3583377 D1 08-08-1991	
		EP 0182583 A2 28-05-1986	
		JP 1502875 C 28-06-1989	
		JP 61119765 A 06-06-1986	
		JP 63050463 B 07-10-1988	
US 5942007	A	24-08-1999	US 5865852 A 02-02-1999
		AT 215631 T 15-04-2002	
		AU 4993599 A 07-02-2000	
		AU 5101799 A 07-02-2000	
		BR 9912088 A 10-04-2001	
		BR 9912811 A 02-05-2001	
		CN 1309733 T 22-08-2001	
		CN 1309734 T 22-08-2001	
		DE 69901179 D1 08-05-2002	
		DK 1084289 T3 24-06-2002	
		EP 1084289 A1 21-03-2001	
		EP 1092056 A1 18-04-2001	
		HU 0102648 A2 28-12-2001	
		NO 20010231 A 14-03-2001	
		NO 20010232 A 14-03-2001	
		PL 345504 A1 17-12-2001	
		PL 345509 A1 17-12-2001	
		TR 200100312 T2 23-07-2001	
		TR 200100318 T2 21-08-2001	
		WO 0004221 A1 27-01-2000	
		WO 0004222 A1 27-01-2000	
		US 6063135 A 16-05-2000	
		US 6042617 A 28-03-2000	
		US 6056789 A 02-05-2000	
		US 6042618 A 28-03-2000	
		US 6086635 A 11-07-2000	
		US 6059845 A 09-05-2000	

**THIS PAGE BLANK (USPTO)**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**THIS PAGE BLANK (USPTO)**